

Garriock Bros. Ltd.

SHETLAND DIVISION - New Agricultural Sales

LT-A750XP King Quad Automatic

Dimensions and Weights

Overall length: 2115mm (83.3in)
Overall width: 1210mm (47.6in)
Overall height: 1285mm (50.6in)
Wheelbase: 1285mm (50.6in)
Seat height: 920mm (36.2in)
Kerb Mass: 305kg (672.4lbs)
Fuel capacity: 17.5litres (3.8 UK gallons)

Engine Specifications

Engine capacity: 722cc
Engine: 4-stroke, single cylinder, liquid cooled, DOHC, 4-valve
Bore: 104.0mm x 85.0mm
Compression ratio: 10.0 : 1
Lubrication: Wet sump
Ignition: Electronic ignition (CDI)
Fuel system: Fuel injection
Starter: Electric
Transmission: Automatic, V-belt, 2-speed forward with reverse
Drive: Shaft drive

Chassis Specifications

Front suspension: Independent double wishbone, 5-way preload adjustment
Rear suspension: Independent double wishbone, 5-way preload adjustment
Front brakes: Disc, twin
Rear brakes: Sealed oil-bathed multi-disc
Front tyres: AT25 x 8-12
Rear tyres: AT25 x 10-12

More Information

This KingQuad uses a 722cc fuel-injected and liquid-cooled engine with four valves and dual-overhead cams. The single-cylinder four-stroke engine is canted forward 48 degrees in the chassis, the optimum placement to deliver the most efficient fuel-air intake and to contribute to keep the machine's center of gravity low.

Fully independent suspension - front and rear - delivers the optimum traction and suspension comfort for your needs. Shock absorbers at all four corners are adjustable for five different preload settings and can be easily adjustable out on the trail or in the field as conditions require.