

# Garriock Bros. Ltd.

**SHETLAND DIVISION - New Agricultural Sales**

## A Series Tractors

The Valtra A Series has been engineered to be extremely strong and reliable. This is a strong, lightweight and extremely agile tractor that delivers the performance you need to carry out your tasks as efficiently as possible. The entire range of A Series tractors is also available in two wheel drive.



| MODEL   | A72n/A72L                | A82n/A82L   | A92n/A92L                 |
|---|--------------------------|---|---------------------------|
| <b>Engine Type</b>  | 33DTA                    | 44DTA   | 44DTA                     |
| Max power, kW/hp/rpm*   | 54/74/2270<br>58/79/2150 | 65/88/2270<br>68/92/2150                                | 75/101/2270<br>72/98/2150 |
| Max torque Nm/rpm   | 296/1400<br>310/1400     | 324/1400<br>355/1400                                    | 360/1400<br>360/1400      |
| No. of cylinders  | 3                        | 4   | 4                         |
| Capacity, l   | 3,3                      | 4,4   | 4,4                       |
| <ul style="list-style-type: none"> <li>• Straightforward powertrain design</li> <li>• Excellent efficiency</li> <li>• HiShift button-operated clutch control - saves pressing clutch pedal</li> <li>• Forward/reverse shuttle</li> <li>• Ideal ratios for working speeds</li> <li>• Four-wheel-braking</li> </ul> |                          |   |                           |
| <b>Power transmission</b>   |                          | <b>Fully synchronized</b>                               |                           |
| Gears forward/reverse   |                          | 12/12   |                           |
| HiShift   |                          | option/-  |                           |
| PTO r/min   |                          | 540+540E / 540+1000                                     |                           |
| <b>Hydraulic</b>  |                          | <b>Separate hydraulics oil.</b>                         |                           |
|   |                          | <b>Max. amount of oil for external hydraulics 24 l.</b> |                           |
| Max lifting force, kN   | 28                       | 33  | 33                        |
| Max lifting power with extra cylinder, kN   | 33                       | -   | -                         |
| Max pump capacity, l/min  | 55                       | 55  | 55                        |